



Aqua Family

iLUMi by CO POWERQ









AQUA FLEX: STATIC WHITE



Color Temperature













Main Application



Outdoors

Color Quality

• CRI 80 •

SDCM 3

Controls

ON/OFF

Other Exteriors



Residential Spaces



Commercial Environments



Offices




Architectural & Specialty Design



Hospitality



Healthcare Facilities



FEATURES

Aqua Flex is curve glazer designed to illuminate the conical walls and curved facades creating an accentuating light effect with its precise optical design and adjustable modules. The smaller pitch design, side bend capabilities and the two mounting profiles ensure Aqua Flex suitable for various curved surfaces.

ACCESSORIES

LEAD-IN CABLE



Length (mm)	Application	Cable End		Conductor Size	Region
300				0.075	_
2000				2x0.75mm ²	Europe
6000	Power Lead	Female	Bare Wire		
300			WIIC	0.404140	110.4
2000				2x18AWG	USA
6000					

JUMPER CABLE



Length (mm)	Application	Cable End		Conductor Size	Region
300				0.075	_
600				2x0.75mm ²	Europe
1800	Power Extension	Female	Male		
300	LATERISION			0.404440	110.4
600				2x18AWG	USA
1800					

SUMMARY

FEATURES			
Color Temperature	2700K, 3000K, 3500k, 4000K, 5000K, 5700K, 6500K		
Length of the Module	300mm, 600mm, 1200mm (7 Diodes per foot)		
Optics	15°, 20°, 30°, 20°x40°, 20°x50°		
Dimming	ON/OFF		
IP Rate	IP66		

MECHANICAL			
Housing Material	Polycarbonate		
Connecting Body	Thermoplastic polyurethane (TPU)		
Lens Material and Cover	Optical grade PMMA		
Surface Color	Black		

LUMINAIRE PERFORMANCE			
Color Consistency	3 SDCM		
Color Rendering	CRI80		
Lumen Maintenance	L70 50,000hrs @25°C		
Lumen Efficiency	930 lm per foot @3000K CCT, CRI80, 15°		


ELECTRICAL	
Voltage	DC 24V
Power Consumption	11.25W / foot


SYSTEM			
The maximum number of connected modules (7 diodes per module) in a daisy chain			
Power / Module	11.25W		
Input voltage	24V		
Max. run length includes power feed to the end of the fixtures in the daisy chain	15 Meters		
Max. no of modules of fixtures can be clusted on a single contiguours run	9 modules		
Max. power allowable in a daisy chain	108W		

Remark: The above values and number are only typical values. Actual number may vary due to the cable lengths and signal source.

The core in the power and data cable are colored according to the following table			
Cable	Power lead in/ Power extension Cable		
Dimming	ON/OFF		
Function	DC+	DC-	
Core(US)	Red	Black	
Wire Size	18AWG	18AWG	
Core(EU)	Brown	Blue	
Wire Size	0.75mm²	0.75mm²	


MOUNTING ACCESSORIES: TREE MOUNT






Description: Flexible metal mounting adjustable clip for Cobra Flex Washer


Top View





MOUNTING ACCESSORIES: WALL MOUNT





Description: Adjustable holder for Cobra Flex Washer

3D Views

